



Modular 60-W and Modular 60-277

IP68 rated 12 Volt DC Power Supply



The Mod 60-W and Mod 60-277 are IP68 (Ingress Protection) rated. The IP68 rating refers to resistance to the intrusion of water, even in harsh environments such as rooftops and areas exposed to heavy rain or snow. This innovative power supply is robust, flexible, extremely weather resistant, auto-sensing and carries UL recognition for dry, damp and wet locations.

- IP68 Rated - Ingress Protection 68 is verified resistance to the intrusion of water, even in harsh environments
- Operating Temperatures -40° C to 60° C
- Auto-resetting – No fuses to replace or circuit breaker to reset. Short Circuit Protection automatically resets when short condition is corrected
- Simple secondary hook-ups – no minimum load, no dip-switches and no load balancing required
- Modular design – cluster with standard J-boxes to create multiple 60 W legs
- Rugged, compact design
- UL recognition for dry, damp and wet locations
- For use with all SloanLED channel letter modules, ThinLED, ColorLINE, FlexiBRITE, PosterBOX Modules and SignBOX Lights

Item Description	Part # Number	Nominal Input Voltage	Input Current	Power Output	Enclosure Spec			Overall Dimensions L x W x H
					Dry	Damp	Wet	
Modular 60-W	701507-MODW	100-240 V	1.0 A	60 W	X	X	X	9 in x 2.5 in x 1.5 in
Modular 60-277	701507-MOD277	277-347 V	0.5 A	60 W	X	X	X	10.5 in x 2.5 in x 1.5 in

