

|                                |  |
|--------------------------------|--|
| <b>Model no.</b>               | LPS-12E30  |
| <b>Input voltage</b>           | 170-250 VAC 50/60 Hz   |
| <b>Max. power</b>              | 30 W max   |
| <b>Output type</b>             | Constant voltage   |
| <b>Dimming</b>                 | No   |
| <b>Built-in active PFC</b>     | No   |
| <b>Power factor</b>            | Low  |
| <b>Efficiency</b>              | 86%  |
| <b>AC inrush current(max.)</b> | Cold start, 40A@230VAC   |
| <b>Output voltage</b>          | 12VDC $\pm$ 5%   |
| <b>Output current</b>          | 2.5 A max  |
| <b>Overload protection</b>     | 105% hiccup mode, auto-recovery  |
| <b>Over voltage protection</b> | 120% rated output voltage  |
| <b>Withstand voltage</b>       | I/P~O/P:1.5kVAC, 1 minute  |
| <b>Operating temperature</b>   | -25~40°C   |
| <b>Installation</b>            | Outdoor waterproof   |
| <b>IP rating</b>               | IP 66  |
| <b>Cooling</b>                 | Free air convection  |
| <b>Certificates/standards</b>  | CE   |
| <b>Connection input/output</b> | Input:0.75mm <sup>2</sup> x3 (18cm) / Output:0.75mm <sup>2</sup> x2 (18cm) |
| <b>Dimensions(L*W*H)</b>       | 220*32*22 mm   |
| <b>Weight(kg)</b>              | 0.3100   |
| <b>Packing information</b>     | 50 Pcs/ Carton, G.W 15.5KG   |