

REGUsign® P 20 Stencil Paper, self-adhesive, with Backing Paper

Description	<i>Material</i>	- Impregnated special stencil paper for paint masks, self-adhesive, with siliconized release liner.
	<i>Application</i>	- Paint masks, cut by plotters or manually, for solvent based or water based laquers, for use on even surfaces like: - Painted metal, tarpaulin, foam boards and other plastic boards, wood, glass, and many other surfaces.
	<i>Market</i>	- Painters - Paint shops - Sign makers, shop builders
	<i>Properties</i>	- High precision edges, - Simple weeding of small and large characters, - Perfect adhesion on the above mentioned surfaces, - No curl of the open edges with aqueous or solvent based laquers, - Precise edges even after long drying time, - Multiple layers of paint possible, - Can be removed without residues.
Usage	<i>Preparation</i>	The surfaces must be dry and free of dust, grease, silicone or other impurities which could influence the adhesion of the mask or the paint.
	<i>Temperatures</i>	The temperature during the application must reach at least 15°C.
	<i>Cutting</i>	The best pressure of the knife is reached, if fine details are easy to weed and the release liner is not cut.
	<i>Weeding</i>	The positive parts of the mask are removed with tweezers, a needle, a knife or any other suitable tool.
	<i>Mounting</i>	A medium tack application tape (film or paper) should be used for mounting.
	<i>Laquering</i>	With a brush or a roller or by air brush, in multiple layers if required. To achieve a good painting it is important to work thoroughly and to choose the right degree of dilution of the paint as well as a paint thinner adapted for the application. For this reason the recommendations of the paint manufacturer must be observed imperatively.
	<i>Removing</i>	The paint mask can only be removed after sufficient drying of the paint.

Technical Data

<i>Substrate</i>	Impregnated special paper
<i>Type of adhesive</i>	Natural caoutchouc, blue coloured
<i>Adhesion strength</i>	~ 1,5 N / 25mm (A.F.E.R.A)
<i>Release liner</i>	Siliconized paper, yellow, 90 - 95g/m ²
<i>Overall thickness</i>	~ 190µm
<i>Temperature range</i>	70°C max.
<i>Available sizes</i>	300 mm x 50 m. 600 mm x 50 m. 1200 mm x 50m.

Storage

REGUsign must be kept in a dark, cool and dry place.

Disposal

The left-over pieces of paper can be treated as industrial waste and incinerated. Nevertheless, it is absolutely necessary to follow the local regulations in force in the waste treatment plants.